



STANDARD MOUNTING HOLES AVAILABLE
*** MAXIMUM VERTICAL LOADING 20 LBS.**

Detail Dimensions Pg. 42 & 43

PLEASE DESIGNATE MATERIAL

A = ALUMINUM
 C = CAST IRON

POSITIVE LOCKING OPTION AVAILABLE

MODEL #	A		B		C		D		E		F	G	H	M	J		K		RAILSET	WEIGHT (LBS)		MAX CC (LBS)
	WIDTH	APL	FPL	TRVL	LC	LK	LEP	OEP	HEIGHT	THREAD DIA-PIT					C DIA	K DIA	C LEN	K LEN		A	C	
L(A/C)2-3-1 (C/K)	2.0 50.8	3.0 76.2	2.0 50.8	1.0 25.4	6.125 155.5	5.5 139.7	0.63 16.0	0.25 6.35	0.98 25.0	#10-40	2.00 50.8	0.88 22.2	2.25 57.2	1.63 41.3	RS118-02-07-C	0.8	2.0	174*				
L(A/C)2-4-1 (C/K)	2.0 50.8	4.0 101.6	3.0 76.2	1.0 25.4	7.125 180.9	6.5 165.1	0.63 16.0	0.25 6.35	0.98 25.0	#10-40	2.00 50.8	0.88 22.2	2.25 57.2	1.63 41.3	RS118-03-12-C	1.1	2.7	348*				
L(A/C)2-6-2 (C/K)	2.0 50.8	6.0 152.4	4.0 101.6	2.0 50.8	8.125 206.3	8.5 190.5	0.63 16.0	0.25 6.35	0.98 25.0	#10-40	2.00 50.8	0.88 22.2	2.25 57.2	1.63 41.3	RS118-04-15-C	1.5	3.3	406*				
L(A/C)3-4-1 (C/K)	3.0 76.2	4.0 101.6	3.0 76.2	1.0 25.4	7.25 184.1	6.87 174.4	0.63 16.0	0.25 6.35	1.25 31.7	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118-03-12-C	1.8	4.2	348*				
L(A/C)3-5-1 (C/K)	3.0 76.2	5.0 127.0	4.0 101.6	1.0 25.4	8.25 209.5	7.87 199.8	0.63 16.0	0.25 6.35	1.25 31.7	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118-04-17-C	2.3	5.3	464*				
L(A/C)3-6-2 (C/K)	3.0 76.2	6.0 152.4	4.0 101.6	2.0 50.8	9.25 234.9	8.87 225.2	0.63 16.0	0.25 6.35	1.25 31.7	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118-04-15-C	2.5	6.4	406*				
L(A/C)4-6-1 (C/K)	4.0 101.6	6.0 152.4	5.0 127.0	1.0 25.4	9.25 234.9	8.87 225.2	0.63 16.0	0.25 6.35	1.44 36.5	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118-05-22-C	3.7	8.9	638*				
L(A/C)4-8-2 (C/K)	4.0 101.6	8.0 203.2	6.0 152.4	2.0 50.8	11.25 285.7	10.87 276.0	0.63 16.0	0.25 6.35	1.44 36.5	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118-06-25-C	4.5	12.0	696*				
L(A/C)4-10-2 (C/K)	4.0 101.6	10.0 254.0	8.0 203.2	2.0 50.8	13.25 336.5	12.87 326.8	0.63 16.0	0.25 6.35	1.44 36.5	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118--08-35-C	5.4	13.9	986*				
L(A/C)4-12-3 (C/K)	4.0 101.6	12.0 304.8	9.0 228.6	3.0 76.2	15.25 387.3	14.87 377.6	0.63 16.0	0.25 6.35	1.44 36.5	5/16-40	2.00 50.8	1.09 27.7	2.25 57.2	2.00 50.8	RS118-09-37-C	6.3	16.0	1044*				
L(A/C)6-8-2 (C/K)	6.0 152.4	8.0 203.2	6.0 152.4	2.0 50.8	12.31 312.7	11.37 288.7	0.63 16.0	0.25 6.35	2.0 50.8	5/8-40	2.95 74.9	1.63 41.3	3.44 87.3	2.50 63.5	RS236-06-10-C	10.1	24.8	720				
L(A/C)6-12-4 (C/K)	6.0 152.4	12.0 304.8	8.0 203.2	4.0 101.6	16.31 414.2	15.37 390.3	0.63 16.0	0.25 6.35	2.0 50.8	5/8-40	2.95 74.9	1.63 41.3	3.44 87.3	2.50 63.5	RS236-08-12-C	13.3	32.0	1440				
L(A/C)6-16-6 (C/K)	6.0 152.4	16.0 406.4	10.0 254.0	6.0 152.4	20.31 515.9	19.37 491.9	0.63 16.0	0.25 6.35	2.0 50.8	5/8-40	2.95 74.9	1.63 41.3	3.44 87.3	2.50 63.5	RS236-10-14-C	16.7	42.8	1680				

PLEASE SPECIFY C-CRANK OR K-KNOB

Please consider using **AMERICAN PRODUCTS**

(800) 892-3991